

# ACCESS

## 5565/6580 AS Series

AS series, designed for every possible screen printing field to satisfy not only the accuracy but also cost performance and operation capability.

Intelligent options and wide adoptability make AS-series popular in Film printing market, PCB market, FPD market and Car industry market.



## High Speed, High Precision, Cost performance

### FEATURE

- 4 posts system for accuracy and easy operation
- Registration of printing data
- Squeegee pressure equalizer
- Lift-up for 400mm for cleaning
- High-lift for squeegee/coater
- Frame slot-in from and 6 points lock
- Snow plow system
- High-speed table drive
- Magnetic switch for squeegee stroke
- Stepless-peel off
- Ink wiping system to prevent dripping
- Motor driven off contact
- Preset counter for 2.3times
- Safety device for frame drop
- Hybrid operation panel
- Choice of 2 colors, blue and red
- Squeegee stop timer

### VARIATIONS

- AS-S Semi-automatic
- AS-SY-MIP semi-automatic walking beam system with CCD camera system
- AS-M 3/4 auto with delivery
- AS-A full automatic with walking beam system
- AS-IBA in-line model
- RtoR AS roll to roll model for web

All the specification and parts are subjective to change without notice.

### SPECIFICATION

SPEC.	MODEL	5565	6580
Max. Print area		550×650mm	650×800mm
Max. Frame size		950×950mm	1100×1100mm
Max. Thickness of Substrate		AS-S:20mm/AS-M:M5mm	
Max. Weight of Substrate		3 kg	
Snow plow		± 3°	
Off Contact		0~20mm	
Peel Off		0~20mm	
Frame Lift		400mm	
Squeegee Speed		20~500mm/sec.	
Squeegee Angle		90° ± 30°	
Printing Table		800x800mm	
Weight		850Kg	
EL. Requirement		200V 3Phase 1.5kw 20A	
Air Supply		0.4MPa	



**MINO INTERNATIONAL LTD.**  
4-47-54 NUKUI, NERIMA-KU, TOKYO  
TEL:+81-(0)3-3577-1621  
FAX:+81-(0)3-3577-3326  
WEB:<http://www.mino.co.jp>